

## EASY LINE

DESCRIPTION		TP43 G	TP43 180	TP43 400	TP43 DS	TP43 1500
Drive		Nylon gear	Belt	Belt	Belt	Direct
Rated power	(W)	1100	1100	1400	1250/1700	1100
Number of revolutions	(rpm)	160	180	400	180/400	1500
Brush	(Ø mm)	430	430	430	430	-
Pad holder	(Ø mm)	430	430	430	430	430
Tank capacity	(l.)	15	15	-	15	-
Weight	(Kg)	35	35	35	35	33
Extra weight	(Kg)	10	-	-	-	-
Size	(cm)					
Length		46	46	46	46	66
Height		120	120	120	120	120
Width			56	56	56	56

## HEAVY LINE

DESCRIPTION		TF33	TS43 PLUS	TS50 PLUS	T UHS 1500 S	T UHS 1500 V
Drive		Nylon gear	Steel gear	Steel gear	Direct	Direct
Rated power	(W)	1100	1100/1800/2200	1100/1800/2200	1100	1100
Number of revolutions	(rpm)	160	160	160	1500	1500
Brush	(Ø mm)	330	430	500	-	-
Pad holder	(Ø mm)	330	430	500	480	480
Vacuum system	-	-	-	-	-	•
Tank capacity	(l.)	15	15	15	-	-
Weight	(Kg)	32	42	45	38	38
Extra weight	(Kg)	-	8	8	-	-
Size	(cm)					
Length		46	46	50	54	54
Height		120	120	120	126	126
Width		50	56	56	61	61



Your Better Choice



Your Better Choice

## SINGLE DISC MACHINE RANGE



For maintenance  
&  
heavy duty  
cleaning tasks

SPECIAL ISSUE AMSTERDAM 2014



## EASY LINE



TP43



TP43 G



## HEAVY LINE



TF33




TS43 PLUS



TS50 PLUS



T UHS 1500 V



The TP43 DS 180 or 400 rpm dual speed version is also available



The off-set position of the engine ensures a well-balanced weight distribution, which translates into effortless use for the operator



The operator can adjust the handle at any of the preset levels for best operating posture



Protection for drive system



Water distribution in the middle



Extra weights can be added to enhance scrubbing performance



Large optional tank (15 l.), can be installed without tools. The supports enable it to stand upright, thus facilitate water filling operations



Nylon and steel gear drive



Dust control available



The machine is easily moved, thanks to the special transportation wheels